



TECHNICAL DATA



ÖWAMAT®

	ÖWAMAT® 10	ÖWAMAT® 11	ÖWAMAT® 12	ÖWAMAT® 14	ÖWAMAT® 15	ÖWAMAT® 16
Container volume	10 l	18.6 l	30.6 l	61.3 l	115.5 l	228.4 l
Filling volume with preseparator	-	-	22.7 l	46.3 l	84.3 l	158.8 l
Filling volume without preseparator	4.3 l	11.7 l	20.3 l	41.5 l	72.5 l	137.2 l
Condensate inlet (hose)	2 x G ¹ / ₂ (di = 10 mm)	2 x G ¹ / ₂ (di = 10 mm)	3 x G ¹ / ₂ (di = 10 mm) 1 x G1 (di = 25 mm)	3 x G ¹ / ₂ (di = 10 mm) 1 x G1 (di = 25 mm)	3 x G ¹ / ₂ (di = 13 mm) 1 x G1 (di = 25 mm)	3 x G ¹ / ₂ (di = 13 mm) 1 x G1 (di = 25 mm)
Water outlet (hose)	G ¹ / ₂ (di = 10 mm)	G ¹ / ₂ (di = 10 mm)	G ¹ / ₂ (di = 13 mm)	G1 (di = 25 mm)	G1 (di = 25 mm)	G1 (di = 25 mm)
Oil outlet	-	-	DN 25	DN 25	DN 40	DN 40
Oil collector	-	-	2 x 5 l	2 x 5 l	2 x 10 l	2 x 20 l
Weight empty with preseparator	-	-	13.5 kg	18.5 kg	36.5 kg	53 kg
Weight empty without preseparator	3.5 kg	5.75 kg	12 kg	16 kg	32 kg	42 kg
Min./max. temp.	+5 bis +60 °C	+5 bis +60 °C	+5 bis +60 °C	+5 bis +60 °C	+5 bis +60 °C	+5 bis +60 °C
Max. operating pressure at inlet	16 bar	16 bar	16 bar	16 bar	16 bar	16 bar
Prefilter	2.5 l	4.7 l	2.5 l	6.7 l	18.5 l	37.2 l
Mainfilter	2.6 l	4.8 l	5.9 l	11.0 l	20.4 l	40.3 l



ÖWAMAT® 10





ÖWAMAT® 11



ÖWAMAT® 12-16 with preseparator



ÖWAMAT® 12-16 without preseparator



	ÖWAMAT® 10	ÖWAMAT® 11	ÖWAMAT® 12	ÖWAMAT® 14	ÖWAMAT® 15	ÖWAMAT® 16
A	528 mm	595 mm	698 mm	867 mm	1088 mm	1158 mm
B	464 mm	534 mm	719 mm	892 mm	1118 mm	1193 mm
C	290 mm	387 mm	350 mm	410 mm	520 mm	650 mm
D	□ 100 mm	□ 140 mm	544 mm	594 mm	764 mm	939 mm
E	222 mm	260 mm	397 mm	461 mm	573 mm	702 mm
F	110 mm	110 mm	320 mm	420 mm	505 mm	535 mm
G	330 mm	368 mm	340 mm	460 mm	550 mm	580 mm
H	-	-	200 mm	240 mm	270 mm	200 mm